

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

**Claims 1-2 (canceled)**

1           **Claim 3 (currently amended):**   An electronic part  
2   supplying tape, used in a tape feeder arranged in a part  
3   supplying portion of an electronic part mounting apparatus,  
4   for holding electronic parts on a tape member at a constant  
5   pitch and for supplying the electronic parts, comprising:  
6           a first tape member with a first end portion and a  
7   second end portion, and a second tape member with a first  
8   end portion and a second end portion;  
9           a first connecting portion formed on the second end  
10   portion of the first tape member;  
11           a second connecting portion formed on the first end  
12   portion of the second tape member, to be connected to the  
13   first connecting portion formed on the first tape member;  
14           an alignment means for positioning the first  
15   connecting portion and the second connecting portion in a  
16   longitudinal direction, a width direction and a thickness  
17   direction of the tape members, and  
18           a holding means for holding the first connecting  
19   portion and the second connecting portion to each other,

20            wherein the first tape member and the second tape  
21 member are connectable by connecting the first connecting  
22 portion of the first tape member and the second connecting  
23 portion of the second tape member,

24            wherein the first connecting portion of the first tape  
25 member comprises a locking member attachment coupled to the  
26 second end portion of the first tape member, and the second  
27 connecting portion of the second tape member comprises a  
28 locked member attachment coupled to the first end portion  
29 of the second tape member, and

30            wherein the locking member attachment and the locked  
31 member attachment constitute the alignment means.

**Claims 4-6 (canceled)**

1            **Claim 7 (previously presented):** An electronic part  
2 supplying tape according to Claim 3, further comprising:

3            a recessed portion for containing an electronic part  
4 therein, formed at a constant pitch on the tape member,

5            wherein the electronic part supplying tape is supplied  
6 by being wound around a supply reel in a state of  
7 containing the electronic part in the recessed portion.

**Claims 8-9 (canceled)**

1           **Claim 10 (currently amended):**   An electronic part  
2   supplying tape according to Claim 3, wherein said locking  
3   member attachment comprises:

4               a flat plate portion with coupling means for  
5   coupling the locking member attachment to the first tape  
6   member, and

7               at least one engaging member extending from said  
8   flat plate portion for attaching the locking member  
9   attachment to the locked member attachment;

10           wherein said locked member attachment comprises:

11               a stepped plate portion with coupling means for  
12   coupling the locked member attachment to the second tape  
13   member, and

14               at least one engaging hole in said stepped plate  
15   portion for engaging with the engaging member of the  
16   locking member attachment.

1           **Claim 11 (currently amended):**   An electronic part  
2   supplying tape according to Claim 3, wherein said locking  
3   member attachment comprises a flat plate portion with an  
4   engaging member, and

5               said locked member comprises a stepped plate portion  
6   with an engaging hole,

7               wherein said ~~step~~-stepped plate portion comprises a  
8   stepped shape such that a stepped difference between the  
9   locking member attachment plate portion and the locked

10 member plate portion in an up and down direction is not  
11 produced when the engaging fixture engages the engaging  
12 hole.

1           **Claim 12 (new):** An electronic part supplying tape  
2 according to Claim 3,

3           wherein each of said tape members having a plurality  
4 of recessed portions formed at a constant pitch for  
5 containing electronic parts and a plurality of feed holes  
6 formed at a constant pitch for feeding the tape member  
7 pitch by pitch in the tape feeder arrangement, and

8           wherein a feed hole is provided on each of the locked  
9 member attachment and locked member attachment at a  
10 position at which a positional relationship of the feed  
11 hole with a contiguous feed hole corresponds with a regular  
12 feed hole of the tape members at said constant pitch.

1           **Claim 13 (new):** A tape member attachment, used to  
2 connect two electronic part supplying tapes each having a  
3 plurality of recessed portions formed at a constant pitch  
4 for containing electronic parts and a plurality of feed  
5 holes formed at a constant pitch for feeding the tape pitch  
6 by pitch in a tape feeder arrangement in a part supplying  
7 portion of an electronic part mounting apparatus,  
8 comprising:

9           a locking member to be connected to an end portion of  
10   a first tape, and a locked member to be connected to an end  
11   portion of a second tape,

12           said locking member comprising:

13           a plate portion, in correspondence to the width  
14   dimension of the first tape,

15           an engaging member provided on a first end portion of  
16   the locking member plate portion,

17           coupling means provided on a second end portion of the  
18   locking member plate portion for connecting the locking  
19   member to the end portion of the first tape, and

20           a feed hole provided on the locking member plate  
21   portion adjacent to said engaging member and at a position  
22   at which a positional relationship of the locking member  
23   feed hole with a contiguous feed hole corresponds with a  
24   regular feed hole of the first tape at said constant pitch,  
25   and

26           said locked member comprising:

27           a plate portion, in correspondence to the width  
28   dimension of the second tape,

29           an engaging recess provided on a first end portion of  
30   the locked member plate portion for engaging with the  
31   engaging member of the locking member,

32           coupling means provided on a second end portion of the  
33   locked member plate portion for connecting the locked

34 member plate portion to the end portion of the second tape,  
35 and

36 a feed hole provided on the locked member plate  
37 portion adjacent to said engaging recess and at a position  
38 at which a positional relationship of the locked member  
39 feed hole with a contiguous feed hole corresponds with a  
40 regular feed hole of the second tape at said constant  
41 pitch,

42 wherein said locked member is connected to said locked  
43 member by engaging said engaging member into said engaging  
44 recess, and

45 wherein, when said locking member is connected to said  
46 first tape member and said locked member is connected to  
47 said second tape member, said first tape is connected to  
48 and aligned with said second tape in a longitudinal  
49 direction, a width direction and a thickness direction by  
50 engaging said engaging member into said engaging recess.